

Part Number
60-105212-93X
Coverstock
ConneXion Reactive
2-Color Pearl
Red / Silver Pearl
Hardness: 76-78
Factory Finish
4,000 Micro Pad

Core Dynamics @ 16#
Two-component
Symmetrical Core
RG max: 2.514
RG min: 2.469
RG diff: 0.045
Average RG: 2.6 of 10

Performance
Hook Potential: 160
Length: 110
Typical Breakpoint
Shape: 95
Chart Position: R - 3
Available Weights
12-16 Pounds

Core: The new ultra low RG **Paragon** core was designed with two intentions. First, lower the RG to create a faster revving core that will provide improved mid-lane traction. And second, raise the RG differential to increase the track flare potential which will generate more overall hook with standard layouts and the use of interchangeable thumb sleeves.

Coverstock: The **Wild Thing** utilizes **ConneXion** coverstock known for its unbelievable traction response from foul line to head pin. The aggressive connection of the **Wild Thing** to the lane surface inspires confidence in the ball reaction that allows bowlers to play the lanes the way they want to.

Ball Motion: The **Wild Thing** and its new ultra low RG core system improves the adhesion of **ConneXion** coverstock to accelerate the response to friction and turn its attack loose on the pins. This core/coverstock combination allows the **Wild Thing** to generate a shape never seen before in the Brunswick line.

Wild Thing... I Think I Love You !!

Micro Finishing Pads: The bowling industry is starting to embrace the surface finishes created by 2000-grit and 4000-grit abrasives. These abrasives create a glossy finish that many bowlers would assume are polished with a wax or similar compound. The benefit to the bowler is that these finishes create length similar to balls coated with compound finishes, but are better able to handle carrydown. The **Wild Thing** is finished with 4000-grit Abrasive pads driven by the new Haus high speed bowling ball resurfacing machine.

Reaction Characteristics

Out of the Box: With its 4000-grit micro pad finish, the **Wild Thing** will provide excellent length and a strong back-end reaction to match up on medium to oily lane conditions for a wide range of bowling styles.

If your Wild Thing goes too long: Shiny surface finishes sometimes cause the ball to go too long before breaking. To get your **Wild Thing** rolling sooner, dull the surface with a 2000-grit micro pad to increase hooking action. To further increase hooking action, use a rougher abrasive to create an earlier reaction.

If your Wild Thing hooks too early: Polish your **Wild Thing** with Brunswick's Factory Finish High Gloss Polish to increase length.

For the most up to date Product Line Information go to www.brunswickbowling.com/balls

Maintaining Your Ball Reaction

Brunswick recommends the following procedures to maintain and restore the reaction characteristic of your Brunswick bowling balls:

--Clean your Brunswick ball with **Brunswick Remove All** or similar ball cleaner after every use to reduce oil absorption.

--If you think your Brunswick ball has lost some of its "Out of the Box" reaction, restore the ball to its original factory finish listed on the product information sheet. This is especially important for balls that are highly sanded or polished.

Sand to 400-grit then use **Factory Finish High Gloss Polish by Brunswick** to restore the original factory finish on high gloss polish balls. Sand to 220-grit then use **Factory Finish Rough Buff by Brunswick** to restore the original factory finish on rough buff balls. For dull balls, wet sand with the sandpaper listed on the product information sheet.

--If there is a visible track on your ball, have your Pro Shop use a Haus or similar resurfacing machine to remove the track then restore the ball to its original factory finish. This service is available, for a fee, at many Pro Shops.

--If your ball has more than 50 games on it, you may be able to increase mid-lane and back-end hooking action by removing oil from the coverstock. Remove the oil from the ball by gently warming it with either the **Revivor** or **Rejuvenator** Pro Shop devices that have been designed for this purpose. The service is available, for a fee, at many Pro Shops.

Brunswick testing has shown that by combining the restoration of the factory finish, resurfacing of the track and oil removal, your Brunswick ball can maintain its original "Out of the Box" reaction for hundreds of games.

Do not use a home oven to remove oil. Temperatures cannot be adequately controlled and the ball may crack.

--Absorbent materials sold by other bowling ball manufacturers to remove oil can also be used on Brunswick bowling balls.

Information to date seems to indicate that absorbent materials have a more limited ability to remove oil than warming.

You may be disappointed with results on heavily oil soaked balls.

Note: Oil soaked balls tend to traction less in the oil and respond less to the dry boards on the lane. If you are matching-up using an oil soaked ball on wet/dry or broken down lane conditions, removing the oil from the ball will significantly change your match-up and possibly create undesirable over reactions.

Ball Comparisons

Want to compare the performance of this ball to other Brunswick balls?

Go to our website at www.brunswickbowling.com. Click on **Balls**, then click on **Pro Shop Information**.






This page contains a link to the **Brunswick Ball Comparison Chart**. This chart allows you to see, at a glance, the performance of all Brunswick balls relative to each other, defined by their **Hook Potential** and **Arc Characteristics**.

There's also an essay to help explain and guide you through the chart.

Lightweight Engineering

At Brunswick, the unique core shape of each individual ball is used for weights from 14 to 16 pounds.

This approach to lightweight ball engineering provides bowlers with consistent ball reaction characteristics across this weight range. At 12 & 13 pounds, Brunswick uses a generic core shape with a RG-differential that is close enough to the 14-16 pound shape so that the same drilling instructions can be used.

Weight	16#	15#	14#	13#	12#	11#	10#
Core Shape						Not Available	Not Available
RG-max.	2.514	2.530	2.552	2.625	2.648		
RG-min.	2.469	2.486	2.509	2.585	2.608		
RG-diff.	0.045	0.044	0.043	0.040	0.040		